



# MACHINE CONSTRUCTION

AGRICULTURE    IRRIGATION    EARTH MOVING

## AP SCRAPER APS 15



### Specifications machine overall

Capacity heaped [m³]	15
Capacity struck [m³]	10,5
Rated load (net) [kg]	27.000
Cutting width [mm]	3000
Overall width [mm]	3500
Overall length [mm]	7650
Overall height [mm]	2600
Weight empty [kg]	12.500
Max. weight loaded [kg]	39.500
(Un)loading type	Fixed knife pivot ejection (bucket on grade filling and dumping)

### Technical requirements

Min. drawbar horsepower tractor		280 PK
Max. operating weight tractor [kg]		25.000
Weight distribution carried by tractor		1/3 of machine weight
<b>Hydraulic requirements</b>		
Hydraulic connection, valve	standard	1/2" quick connect, 2 functions, hydraulic control valves



## AP SCRAPER APS 15

### Technical specifications

Tire type / size	standard	4 x 235-25 Michelin radial tire XADN tl
Optional tires		235-25 Techking diagonal tire 235-25 BKT radial tire
Rims and axles		Heavy-duty independent rotating and adjustable rims, 10 tons each
Hitch	standard	Rotatable heavy duty hitch with 50mm pin
Suspension	standard	Hydraulic accumulator suspension
Electrical system road light, turn and stop light	standard	12V
Electrical connection for 2e scraper	optional	At the back of the scraper
Safety sign width (at back)	standard	Diagonal yellow orange striping
Work light	optional	12 / 24V
Safety light	optional	Orange beacon
Cutting blade	standard	Self-sharpening, reversible, Hardox 470

### Additional options

Push block (at the back)	optional	Heavy steel block
Brake system (park system)	optional	Disk brake for each wheel, electric or hydraulic controlled, connection to tractors brake system
Automatic grease system	optional	Groenenveld automatic grease system for all pivots and cilinders
GPS Topcon single system	optional	
Laser control Topcon	optional	
Electric controlled funtions	optional	Joystick control (for laser or GPS)
GPS or laser platform	optional	Standard platform used to mount laser or GPS masts
Company colours	optional	On request

